

# SMART PLUG

Datasheet



SCHUKO

TYPE E



The NodOn® Smart Plug can be controlled by a Z-Wave® or Z-Wave Plus® home automation gateway or directly through others Z-Wave® or Z-Wave Plus® devices such as The Soft Remote, The NodOn® Wall Switch or the NodOn® Octan Remote. It is available in German (Schuko) or French Standard (Type E).

## TECHNICAL DATA

Power supply: 230V AC +/-10% - 50Hz  
Maximum output power: 3000W continuous / 3500W temporary (Resistive load)  
Self-consumption: <1W  
Operational temperature: 0°C to 40°C - Altitude : 2000m  
Radio protocol Z-Wave®: 868.4MHz – 500 Series – Compliant Z-Wave Plus® SDK 06.51.01  
Range: 40m indoor / 80m outdoor  
Main power outage detection and notification  
Dimensions: 104\*51\*36mm  
Warranty 2 years

## STANDARDS

EN61058 2002+AE2008: 2008	DIN 0620 -2-1: 2013 (Schuko)	EN300220-1 V2.4.1: 2012
NF C 61-314 2008+AE2010: 2010 (Type E)	EN301489-1 V1.6.1: 2013	EN300220-2 V1.9.2: 2011
DIN 0620 -1: 2013 (Schuko)	EN301489-2 V1.6.1: 2013	

## REFERENCES NUMBERS

ASP-3-1-00 - EAN : 3700313920190 – Type E  
ASP-3-1-10 - EAN : 3700313920206 – Schuko